# UNCLASSIFIED

AD 4 2 0 7 0 0

## DEFENSE DOCUMENTATION CENTER

**FOR** 


SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.



Report No. RE-TR-63-13
Copy

ATMOSPHERIC TRANSMITTANCE CURVES
FOR SEVERAL METEOROLOGICAL CONDITIONS

25 March 1963



U S ARMY MISSILE COMMAND REDSTONE ARSENAL, ALABAMA

## DDC Availability Notice

Qualified requesters may obtain copies of this report from the Defense Documentation Center for Scientific and Technical Information, Cameron Station, Alexandria, Virginia 22314.

## Destruction Notice

Destroy; do not return.

# ATMOSPHERIC TRANSMITTANCE CURVES FOR SEVERAL METEOROLOGICAL CONDITIONS

bу

M. W. Harper

Electro-Optical Branch
Electromagnetics Laboratory
Directorate of Research and Development
U. S. Army Missile Command
Redstone Arsenal, Alabama

#### **ABSTRACT**

This report is intended to provide a tool for use in designing infrared systems, and is not a theoretical treatise on atmospheric effects in optical transmission.

Spectral transmission curves are furnished for several different combinations of atmospheric conditions and ranges. These infrared spectral transmission curves were calculated assuming the earth to be flat for the ranges of interest, and assuming the infrared systems to be at sea level.

## TABLE OF CONTENTS

					Page					
I. INTRODUCTION										
II.	II. DISCUSSION									
III.	CONCLUSIO	CONCLUSIONS AND RECOMMENDATIONS								
LIST OF ILLUSTRATIONS										
Table										
I.	I. Sample Calculated Date									
Figure										
_	l. Path for 1 mm of Water (ft/mm)									
Atmospheric Transmission Curves:										
	Range	Visibility	Relative Humidity	Temperature						
2.	. l km	10 km	40%	70°F	7					
3	. 2 km	10 km	40%	70°F	9					
4	. 3 km	l0 km	40%	70°F	11					
5	. 4 km	10 km	40%	70°F	13					
6	. 5 km	10 km	40%	70°F	15					
7	. l km	5 km	90%	100°F	17					
8	. 2 km	5 km	90%	100°F	19					
9	. 3 km	5 km	90%	100°F	21					
10	. 4 km	5 km	90%	100°F	23					
11	. 5 km	5 km	90%	100°F	25					
12	. l km	5 km	40%	70°F	27					
13	. 2 km	5 km	40%	<b>7</b> 0°F	29					
14	. 3 km	5 km	40%	70°F	31					
15	. 4 km	5 km	40%	70°F	33					
16	. 5 km	5 km	40%	70°F	35					
17	. l km	10 km	90%	100°F	37					
18		10 km	90%	100°F	39					
19		10 km	90%	100°F	41					
20 21		10 km 10 km	90% 90%	100°F 100°F	43 45					

#### I. INTRODUCTION

During the course of calculating infrared spectral transmission values, it became clear that some means was needed to obtain these spectral transmission values more quickly. This report is intended to provide a tool for use in designing infrared systems, and is not a theoretical treatise on atmospheric effects in optical transmission. This report furnishes spectral transmission curves for several different combinations of atmospheric conditions and ranges.

These infrared spectral transmission curves were calculated assuming the earth to be flat for the ranges of interest, and assuming the infrared systems to be at sea level.

#### II. DISCUSSION

The main factors in atmospheric infrared attenuation are absorption by water vapor, carbon dioxide, ozone, and scattering by airborne particles. The water vapor content (Figure 1) of the atmosphere is weather-dependent. Thus, either the amount of water vapor between the target and observer (the optical thickness) must be known for a particular problem, or an average-weather assumption must be made. For simplicity of calculations, average-day values and bad-day values were assumed for water vapor content and visibility. The carbon dioxide content of the atmosphere was taken to be  $3.2 \times 10^{-4}$  parts per unit volume of air. The ozone content of the atmosphere was taken to be .002 mm per kilometer.

The scattering coefficient of transmission has to be calculated as

a function of wavelength, range and visibility  $\begin{bmatrix} T_{si} = e^{\frac{3.91}{V} \left(\frac{\lambda_i}{.55}\right)^{-q}} R \end{bmatrix}$  where

 $T_{si}$  = Transmission due to scattering at wavelength (i).

V = Visibility (kilometers)

 $q = .585 V^{1/3}$ 

i = Wavelength (microns)

R = Range (kilometers)

This relationship enables us to compute the transmission at the midpoint of window i for any value of R if the visibility is known.

(Sample Calculation)

$$V = 5 \text{ km.} \quad q = 1.0, \quad i = 1 \text{ micron,} \quad R = 3 \text{ km}$$

$$T_{si} = e^{-\frac{3.91}{V} \left(\frac{\Lambda_{i}}{.55}\right)^{-Q} R}$$

$$T_{s(1\mu)} = e^{-\frac{3.91}{5} \left(\frac{1.0}{.55}\right)^{-1.0} (3)}$$

$$= e^{-\frac{.782 \left(\frac{.55}{1.0}\right)}{= e^{-\frac{1.29}{5}}}$$

$$= e^{-\frac{1.29}{5}}$$

$$= .275$$

Precipitable  $H_2O$  is taken from Figure 1 of this report. With 90% relative humidity and  $100^{\circ}F$ , temperature, there is 1 mm  $H_2O$  for every 75 feet of path length. Dividing range by this factor gives the total precipitable  $H_2O$  for a 3-km range.

Total Precipitable 
$$H_2O$$
 =  $\frac{\text{Range (feet)}}{\text{feet/mm precipitable } H_2O}$   
=  $\frac{9842 \text{ feet}}{75 \text{ feet/l mm}}$   
= 131.22 mm

Transmission due to absorption by water vapor is plotted as a function of precipitable  $H_2O$  versus wavelength, as shown in Figure 8, Reference 7. Knowing that the precipitable  $H_2O$  is 13.1 cm,  $T_{H_2O(1\mu)}$  is .64.

Transmission due to absorption by carbon dioxide is plotted as a function of range versus wavelength (Figure 17, Reference 7). Knowing the range is 3 km,  $T_{\rm CO_2(1u)}$  is 100%.

From Figure 7, Reference 7, there is .002 mm of ozone at STP per kilometer at sea level. The total amount of ozone for XKM range equals the product of XKM and ZM.M of ozone.

Total ozone for 3-km range = 3 km·.002 mm/km = .006 mm

Knowing the amount of ozone in the path length, the transmission due to absorption by ozone is 100% at one micron (Figure 23, Reference 7).

After the coefficients of transmission due to absorption by water vapor, carbon dioxide, ozone, and scattering have been found, the atmospheric transmission is calculated as the product of these functions:

$$T_{a(\lambda)}$$
 =  $T_{H_2O(\lambda)} \cdot T_{CO_2(\lambda)} \cdot T_{O_3(\lambda)} \cdot T_{si}$   
 $T_{a(1.0_{\mu})}$  = (.64) · (1.00) · (1.00) · (.28)  
= .18  
= 18%

#### III. CONCLUSIONS AND RECOMMENDATIONS

Value for  $T_{H_2O(\lambda)}$ ,  $T_{O_3(\lambda)}$ ,  $T_{CO_2(\lambda)}$ , and  $T_{si}$  were calculated at one-tenth micronintervals. The resolution of the transmission curves is, therefore, not much better than  $\pm$ .l micron. Moreover, the apparent smoothing of the curves used as source material for this report (Reference 7) suggests that the results be applied judiciously, especially for very narrowband applications. It should be remembered that the atmospheric conditions considered herein are highly generalized and worst-case conditions may reduce transmission far below the values shown.

;

## TABLE OF CONTENTS

					Page			
I.	INTRODUC	TION		• • • • • • • • • • • • • • • • • •	1			
II.	II. DISCUSSION							
III.	CONCLUSIO	NCLUSIONS AND RECOMMENDATIONS						
		т	icm Or II I HCTD A	PIO NIC				
LIST OF ILLUSTRATIONS Table								
I.								
_	Figure							
1	. Path fo	Path for 1 mm of Water (ft/mm)						
	Atmos	Atmospheric Transmission Curves:						
	Range	Visibility	Relative Humidity	Temperature				
2	. l km	10 km	40%	70°F	7			
3	. 2 km	l0 km	40%	70°F	9			
4	. 3 km	10 km	40%	70°F	11			
5	. 4 km	10 km	40%	70°F	13			
6	. 5 km	10 km	40%	70°F	15			
7	. l km	5 km	90%	100°F	17			
8	. 2 km	5 km	90%	100°F	19			
9	. 3 km	5 km	90%	100°F	21			
10	. 4 km	5 km	90%	100°F	23			
11	. 5 km	5 km	90%	100°F	25			
12	. l km	5 km	40%	70°F	27			
13		5 km	40%	70°F	29			
14	. 3 km	5 km	40%	70°F	31			
15	. 4 km	5 km	40%	70°F	33			
16	. 5 km	5 km	40%	70°F	35			
17	'. l km	10 km	90%	100°F	37			
18		10 km	90%	100°F	39			
19		10 km	90%	100°F	41			
20	). 4 km	10 km	90%	100°F	43			
21	. 5 km	10 km	90%	100°F	45			
					iii.			

### I. INTRODUCTION

During the course of calculating infrared spectral transmission values, it became clear that some means was needed to obtain these spectral transmission values more quickly. This report is intended to provide a tool for use in designing infrared systems, and is not a theoretical treatise on atmospheric effects in optical transmission. This report furnishes spectral transmission curves for several different combinations of atmospheric conditions and ranges.

These infrared spectral transmission curves were calculated assuming the earth to be flat for the ranges of interest, and assuming the infrared systems to be at sea level.

#### II. DISCUSSION

The main factors in atmospheric infrared attenuation are absorption by water vapor, carbon dioxide, ozone, and scattering by airborne particles. The water vapor content (Figure 1) of the atmosphere is weather-dependent. Thus, either the amount of water vapor between the target and observer (the optical thickness) must be known for a particular problem, or an average-weather assumption must be made. For simplicity of calculations, average-day values and bad-day values were assumed for water vapor content and visibility. The carbon dioxide content of the atmosphere was taken to be  $3.2 \times 10^{-4}$  parts per unit volume of air. The ozone content of the atmosphere was taken to be .002 mm per kilometer.

The scattering coefficient of transmission has to be calculated as

a function of wavelength, range and visibility  $\begin{bmatrix} T_{si} = e^{-\frac{3.91}{V} \left(\frac{\lambda_i}{.55}\right)^{-q}} \\ R \end{bmatrix}$  where

 $T_{si}$  = Transmission due to scattering at wavelength (i).

V = Visibility (kilometers)

 $q = .585 V^{1/3}$ 

i = Wavelength (microns)

R = Range (kilometers)

This relationship enables us to compute the transmission at the midpoint of window i for any value of R if the visibility is known.

(Sample Calculation)

$$V = 5 \text{ km.} \quad q = 1.0, \quad i = 1 \text{ micron,} \quad R = 3 \text{ km}$$

$$T_{si} = e^{-\frac{3.91}{V} \left(\frac{\lambda_i}{.55}\right)^{-q} R}$$

$$T_{s(1\mu)} = e^{-\frac{3.91}{5} \left(\frac{1.0}{.55}\right)^{-1.0} (3)}$$

$$= e^{-\frac{.782 \left(\frac{.55}{1.0}\right) (3)}{= e^{-\frac{1.29}{1.29}}}$$

$$= .275$$

Precipitable  $H_2O$  is taken from Figure 1 of this report. With 90% relative humidity and  $100^{\circ}F$ . temperature, there is 1 mm  $H_2O$  for every 75 feet of path length. Dividing range by this factor gives the total precipitable  $H_2O$  for a 3-km range.

Total Precipitable 
$$H_2O$$
 =  $\frac{\text{Range (feet)}}{\text{feet/mm precipitable } H_2O}$   
=  $\frac{9842 \text{ feet}}{75 \text{ feet/l mm}}$   
= 131.22 mm

Transmission due to absorption by water vapor is plotted as a function of precipitable  $H_2O$  versus wavelength, as shown in Figure 8, Reference 7. Knowing that the precipitable  $H_2O$  is 13.1 cm,  $T_{H_2O(1\mu)}$  is .64.

Transmission due to absorption by carbon dioxide is plotted as a function of range versus wavelength (Figure 17, Reference 7). Knowing the range is 3 km,  $T_{CO_2(1\mu)}$  is 100%.

From Figure 7, Reference 7, there is .002 mm of ozone at STP per kilometer at sea level. The total amount of ozone for XKM range equals the product of XKM and ZM.M of ozone.

Total ozone for 3-km range = 3 km· .002 mm/km = .006 mm

Knowing the amount of ozone in the path length, the transmission due to absorption by ozone is 100% at one micron (Figure 23, Reference 7).

After the coefficients of transmission due to absorption by water vapor, carbon dioxide, ozone, and scattering have been found, the atmospheric transmission is calculated as the product of these functions:

$$T_{a(\lambda)}$$
 =  $T_{H_{2}O(\lambda)} \cdot T_{CO_{2}(\lambda)} \cdot T_{O_{3}(\lambda)} \cdot T_{si}$   
 $T_{a(1.0_{\mu})}$  = (.64) · (1.00) · (1.00) · (.28)  
= .18  
= 18%

#### III. CONCLUSIONS AND RECOMMENDATIONS

Value for  $T_{H_2O(\lambda)}$ ,  $T_{O_3(\lambda)}$ ,  $T_{CO_2(\lambda)}$ , and  $T_{si}$  were calculated at one-tenth micronintervals. The resolution of the transmission curves is, therefore, not much better than  $\pm$ .l micron. Moreover, the apparent smoothing of the curves used as source material for this report (Reference 7) suggests that the results be applied judiciously, especially for very narrowband applications. It should be remembered that the atmospheric conditions considered herein are highly generalized and worst-case conditions may reduce transmission far below the values shown.

Table I.

SAMPLE CALCULATED DATA

CALCULATED VALUES FOR  $T_{H_2O(\lambda)}$ ,  $T_{CO_2(\lambda)}$ ,  $T_{O_3(\lambda)}$ ,  $T_{si}$  AND  $T_{a(\lambda)}$ 

## METEOROLOGICAL CONDITIONS:

TEMPERATURE - 100°F RELATIVE HUMIDITY - 90% RANGE - 3-km VISIBILITY - 5-km PRECIPITABLE H<sub>2</sub>O - 13.1-cm

Wavelength Micron	$T_{\text{H}_{\mathbf{z}}}O(\lambda)$ $\times$ Decimal	T <sub>CO<sub>2</sub>(λ)</sub> Decimal	$\times \frac{\text{TO}_3(\lambda)}{\text{Decimal}}$	$\times \frac{T_{si}}{Decimal} =$	$T_{a(\lambda)}$ <u>Decimal</u>
. 4	.34	1.00	1.00	.041	.014
. 5	. 50	1.00	1.00	.08	.04
. 6	. 89	1.00	1.00	. 12	. 10
.7	.90	1.00	1.00	.16	. 14
. 8	. 60	1.00	1.00	.20	. 12
. 9	.11	1.00	1.00	. 24	. 02
1.0	. 64	1.00	1.00	.28	.18
1.1	.16	1.00	1.00	.31	. 05
1.2	.33	1.00	1.00	. 34	.11
1.3	.00	1.00	1.00	. 37	.00
1.4	.00	.98	1.00	. 40	.00
1.5	. 85	•99	1.00	. 42	.36
1.6	.98	.98	1.00	. 45	.41
1.7	. 93	•99	1.00	. 47	. 44
1.8	.00	1.00	1.00	. 48	.00
1.9	.04	1.00	1.00	.51	. 02
2.0	. 45	. 89	1.00	. 52	.21
2.1	. 86	.99	1.00	. 54	. 46
2.2	. 93	1.00	1.00	. 56	. 52
2.3	. 86	1.00	1.00	. 57	. 49
2.4	.35	1.00	1.00	. 59	.21
2.5	.00	1.00	1.00	. 59	.00






Figure 1. PATH FOR 1 MM OF WATER (FT/MM




Figure 1. PATH FOR 1 MM OF WATER (FT/MM)






Figure 2. ATMOSPHERIC TRANSMISSION CURVE




Figure 2. ATMOSPHERIC TRANSMISSION CURVE




Figure 3. ATMOSPHERIC TRANSMISSION CU




Figure 3. ATMOSPHERIC TRANSMISSION CURVE




Figure 4. ATMOSPHERIC TRANSMISSION CURVE




Figure 4. ATMOSPHERIC TRANSMISSION CURVE

The second secon






Figure 5. ATMOSPHERIC TRANSMISSION CURVE





Figure 5. ATMOSPHERIC TRANSMISSION CURVE



10

Figure 6. ATMOSPHERIC TRANSMISSION CURVE

3.0 3.5 WAVELENGTH (MICRONS)

4.0

4.5

2.5




Figure 6. ATMOSPHERIC TRANSMISSION CURVE




Figure 7. ATMOSPHERIC TRANSMISSION CURVE




Figure 7. ATMOSPHERIC TRANSMISSION CURVE




Figure 8. ATMOSPHERIC TRANSMISSION CURVE




Figure 8. ATMOSPHERIC TRANSMISSION CURVE




Figure 9. ATMOSPHERIC TRANSMISSION CURVE




Figure 9. ATMOSPHERIC TRANSMISSION CURVE




Figure 10. ATMOSPHERIC TRANSMISSION CUR




Figure 10. ATMOSPHERIC TRANSMISSION CURVE






Figure 11. ATMOSPHERIC TRANSMISSION CURVE




Figure 11. ATMOSPHERIC TRANSMISSION CURVE






Figure 12. ATMOSPHERIC TRANSMISSION CURVE




Figure 12. ATMOSPHERIC TRANSMISSION CURVE






Figure 13. ATMOSPHERIC TRANSMISSION CU




Figure 13. ATMOSPHERIC TRANSMISSION CURVE




Figure 14. ATMOSPHERIC TRANSMISSION CURVE




Figure 14. ATMOSPHERIC TRANSMISSION CURVE




Figure 15. ATMOSPHERIC TRANSMISSION CURVE




Figure 15. ATMOSPHERIC TRANSMISSION CUEVE




Figure 16. ATMOSPHERIC TRANSMISSION CURV




Figure 16. ATMOSPHERIC TRANSMISSION CURVE




Figure 17. ATMOSPHERIC TRANSMISSION CURVE




Figure 17. ATMOSPHERIC TRANSMISSION CURVE

HANNAMORE ARTHUR PROPERTY OF THE PROPERTY OF T




Figure 18. ATMOSPHERIC TRANSMISSION CURVE




Figure 18. ATMOSPHERIC TRANSMISSION CURVE




Figure 19. ATMOSPHERIC TRANSMISSION CURVE




Figure 19. ATMOSPHERIC TRANSMISSION CURVE




Figure 20. ATMOSPHERIC TRANSMISSION CURVE

The thermal and the section of the contract of




Figure 20. ATMOSPHERIC TRANSMISSION CURVE






Figure 21. ATMOSPHERIC TRANSMISSION CURV




Figure 21. ATMOSPHERIC TRANSMISSION CURVE

## REFERENCES

(Reference to Published Reports on Atmospheric Transmission Curves)

- 1. G. J. Zissis, "Fundamentals of Infrared Technology," The University of Michigan (UNCLASSIFIED)
- 2. "Atmospheric Attenuation of 4.3 Micron Carbon-dioxide Emission," May 1959, IRIS Vol. 4, No. 2. (SECRET)
- 3. David M. Gates and Clyde C. Shaw, "Infrared-Transmission of Clouds," 1960, J.D.S.A., Vol. 50, No. 9. (UNCLASSIFIED)
- 4. "Vision Through the Atmosphere," 1952, University of Toronto Press, page 20. (UNCLASSIFIED)
- 5. Elder, Tait, and Strong, "The Infrared Transmission of Atmospheric Windows," 1953, John F. Franklin Institute, Vol. 225, page 189. (UNCLASSIFIED)
- 6. "The Infrared Atmospheric Transmission Problem," 1948, Strong, Johns Hopkins Press, Baltimore. (UNCLASSIFIED)

(Reference to Reports Using Methods for Calculating Atmospheric Transmission Coefficients)

- 7. Thomas Attshuler, "A Procedure for Calculation of Atmospheric Transmission of Infrared," G.E. Rpt. 57, EHCl5. (UNCLASSIFIED)
- 8. Paul W. Kruse, Lawrence D. McGauchlin, Richard B. McQuistan, "Elements of Infrared Technology, Transmission and Detection," 1962, John Wiley and Sons, Inc., New York, London. (UNCLASSIFIED)
- 9. T. L. Attshuler, "MSVD Document 61 SD199," General Electric Company, Valley Forge, Pennsylvania. (UNCLASSIFIED)

## **BIBLIOGRAPHY**

- 1. Thomas Altshuler, "A Procedure for Calculation of Atmospheric Transmission of Infrared," General Electric, May 1957.
- 2. Kruse, McGlauchlin, and McQuistan, "Elements of Infrared Technology, Generation, Transmission, and Detection," John Wiley & Sons, Inc., New York, 1962.

## APPROVED:

N. J. MANGUS

Chief, Electro Optical Branch Electromagnetics Laboratory

Dickowe.

D. E. ROWE

Director, Electromagnetics Laboratory

## **DISTRIBUTION**

	Сору
U. S. Army Missile Command Distribution	
List A for Technical Reports, 11 Mar 63	1-103
AMSMI-R, Mr. McDaniel	104
-RD	105
-RE	106
-REO	107, 113
-REP	114-116
-RES	117-119
-RF	120
-RFE	121-123
-RFC	124
-RH	125
-RHS	126
-RHB	127
-RHA	128-130
-RK	131
-RR	132
-RT	133
-RBL	134-138
-XG	139
-RAP	140

AD Accession No.  AD Accession A strand gives a fraint-fed years.  AD Accession No.
Accession No.  MoSFIERC Command, Directorate of Research by Missile Command, Directorate of Research bacoptine and range as are furnished for several different combined to provide a tool for use in whissile Command, Directorate of Research by Missile Command, Directorate of Research by
ny Missile Command, Directorate of Research I Development, Electromagnetics Laboratory, Istone Arsenal, Alabama MOSPHERIC TRANSMITTANCE CURVES FOR FERAL METEOROLOGICAL CONDITIONS - M. Harper  ny Mal Cmd RE-TR-63-13, 25 Mar 63, 49pp - 1s. Unclassified Report  is report is intended to provide a tool for use in igning infrared systems. Spectral transmission ves are furnished for several different combinans of atmospheric conditions and ranges. These ves were calculated assuming the earth to be took at and the infrared systems to be at sea level.  Accession No.  Accession No.  Accession No.  Accession No.  Harper  NOSPHERIC TRANSMITTANCE CURVES FOR TRAL METEOROLOGICAL CONDITIONS - M. Harper  ny Missile Command, Directorate of Research of MosPHERIC TRANSMITTANCE CURVES FOR TEADER OF TRANSMITTANCE CURVES FOR TRANSMIT Sales at the minister of the several different combinans of atmospheric conditions and ranges. These ves are furnished for several different combinans of atmospheric conditions and ranges. These ves were calculated assuming the earth to be tand infrared systems to be at sea level.
Accession No.  my Missile Command, Directorate of Res I Development, Electromagnetics Laboratistone Arsenal, Alabama MOSPHERIC TRANSMITTANCE CURVES FRAL METEOROLOGICAL CONDITIONS Harper  my Msl Cmd RE-TR-63-13, 25 Mar 63, 4  us. Unclassified Report  is report is intended to provide a tool for igning infrared systems. Spectral transmos of atmospheric conditions and ranges.  ves were calculated assuming the earth to tand the infrared systems to be at sea leves were calculated assuming the earth to tand the infrared systems to be at sea lever and the infrared systems to be at sea level.  Accession No.  Accession No.  Accession No.  Accession No.  Harper  my Missile Command, Directorate of Res I Development, Electromagnetic Laborate distone Arsenal, Alabama  MOSPHERIC TRANSMITTANCE CURVES  WERAL METEOROLOGICAL CONDITIONS  Harper  ny Msl Cmd RE-TR-63-13, 25 Mar 63, 4  us. Unclassified Report  is report is intended to provide a tool for igning infrared systems. Spectral transmoves are furnished for several different corns of atmospheric conditions and ranges.  ves were calculated assuming the earth to and infrared systems to be at sea level.